



# *Sand Star III*

## *Grooming Made Easy*

Boasting a selection of over 50 accessories, Smithco's Sand Star III stands out as the preferred sand groomer for golf course superintendents and grounds directors seeking exceptional traction, heightened stability, and a diverse range of implements. Crafted with top-notch industrial-grade materials, this durable machine is designed for longevity.

### • PERFORMANCE

Optimal raking is achieved with the "Speed Boss" Speed Control System. Spend less time fixing mistakes, leaving your course or field in optimal condition on the first try.

### • PRODUCTIVITY

Both center and rear implements as well as plows, key switches and other controls are located conveniently in operator position. The operator seat and controls are ergonomically designed for safety and comfort, increasing the operator's productivity.

### • OPTIONS

With over 50 accessories and industrial-grade components, Smithco's bunker rakes and groomers are built to last as your course or field changes and grows.

### • INTERCHANGEABILITY

Smithco's Sand Star's are equipped with a single point quick hitch for easy interchangeability of implements and attachments. You spend less time maneuvering equipment and more time getting the job done.

Exceptional Service and Products Since 1967  
[smithco.com](http://smithco.com)

***Smithco***  
WE TAKE YOUR TURF SERIOUSLY

# Sand Star III

## SPECIFICATIONS

# Smithco

United States | 877.833.7648  
International | +1 610.688.4009

### ENGINE

Type	Vanguard V-twin air cooled
Displacement	34.8 in <sup>3</sup> (570 cc)
Rated Horsepower	18 hp (13 kw)
Air Cleaner	Engine mount and remote cyclonic air intake
Cooling	Air cooled
Lubrication	Full pressurized
Oil Filter	Full flow; Spin on type
Electrical System	16 amp, with 12V 300 CCA battery, fuse protected
Fuel Capacity	5 gal (18.9 l)

### SPEED & SOUND

Transport	0-12 mph (0-19.3 kph)
Reverse	0-5 mph (0-8 kph)
Forward	0-12 mph (0-19.3 kph)
Sound Level	87 dba

### TIRES, BRAKES & STEERING

Service Brakes	Dynamic braking through hydrostatic drive train
Tires	22 – 11 x 10.0 Knobby Tire
Parking Brake	Hand operated, 8 in (20 cm) disk type
Steering	Power

### TRACTION DRIVE

Hydraulic System	5 gal (18.9 l)
Hydraulic Cooling	Full flow filter with oil cooler
Traction System	3WD; variable displacement hydraulic pump; individual hydraulic wheel motors with 2-wheel/3-wheel on/off switch

### WEIGHTS & DIMENSIONS

Ground Clearance	5.5-7 in (13-18 cm)
Height	52 in (1.3 m)
Width	58 in (1.5 m)
Length	68 in (1.7 m)
Weight	915 lbs (415 kg)
Wheelbase	42 in (1.1 m)

### PRODUCT CONFIGURATION

Description	3-wheel tricycle design
Levers	Hydraulic engage/disengage lever for rear mounted and center mounted attachments

Distributed by:



[www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)  
[info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)

\*Hong Kong, Macau & Singapore.



Learn More Today!